

NEW

Water-Resistant, Food-Grade Grease-Filled Bearings



Corrosion
resistance

Water-resistant grease helps extend bearing service life
in wet environments.

Bearing
selection

Products
Series

AISI
440C

AISI
304

AISI
630

High-
Silicon

Pure
Titanium

Ceramic

Heat
Resistance

Grease
Free

Low
Torque

Solid
Grease

Water-resistant
Food grade
Grease

Atom
Grease

Vacuum
Grease

Conductive
Grease

Set
Screw

Alignment
Function

Flange
Unit

Guide
Wheel

Spherical
Outer

100

100

ization

es of
Use

Features


1. Uses water-resistant grease
2. Filled with NSF H1 certified grease for food machinery applications
3. Engineered to support HACCP compliant operations

Product Specifications


Standard Specifications	
Inner and Outer Rings	AISI 440C
Balls	AISI 440C
Retainer	AISI 304
Shield	AISI 304
Seal	Nitrile rubber
Lubricant	Water-resistant and food-grade grease

Performance

Durability in High-Moisture Conditions



*The test was completed for 1,000 hours without any issues. Please consult with us before use in liquids other than water, such as antiseptic or cleaning solution. The above performance values are based on our internal test results and are not guaranteed values.



Test Conditions

Bearing	:6004
Temperature	:25°C/77°F
Radial load	:1000N
Rotation speed	:500min ⁻¹
Liquid	:Tap water

Applications

Food processing, cleaning and transport equipment in wet or washdown environments, including exposure to steam and water spray.

Bearing selection

Products Series

AISI 440C

AISI 304

AISI 630

High-Silicon

Pure Titanium

Ceramic

Heat Resistance

Grease Free

Low Torque

Solid Grease

Water-resistant Food grade Grease

Clean room Grease

Vacuum Grease

Conductive Grease

Set Screw

Alignment Function

Flange Unit

Guide Wheel

Spherical Outer ring

6800 6900

SS5200 5200

5800

Customization

Examples of Use


Bearing selection
Products Series
AISI 440C
AISI 304
AISI 630
High-Silicon
Pure Titanium
Ceramic
Heat Resistance
Grease Free
Low Torque
Solid Grease
Water-resistant Food grade Grease
Clean room Grease
Vacuum Grease
Conductive Grease
Set Screw
Alignment Function
Flange Unit
Guide Wheel
Spherical Outer ring
6800 6900
SS5200 5200
5800
Customization
Examples of Use

Composition of bearing number

1 2 3 4 SS 6200 2RS FE				1 SS : Material AISI 440C
				2 Basic number
				3 ZZ : Double steel plate shields 2RS : Double contact rubber seals
				4 FE : Water-resistant and food-grade grease

Table of Dimensions

Bearing Numbers	d	D	B	r min.	Basic Load Ratings		Mass
					C _r	C _{or}	
	mm	mm	mm	mm	N	N	g
SS 6800 FE	10	19	5	0.3	2120	985	5
SS 6900 FE	10	22	6	0.3	2700	1270	9
SS 6000 FE	10	26	8	0.3	4600	1970	18
SS 6200 FE	10	30	9	0.6	5100	2390	31
SS 6300 FE	10	35	11	0.6	8100	3450	52
SS 6801 FE	12	21	5	0.3	1920	1040	6
SS 6901 FE	12	24	6	0.3	2890	1460	10
SS 6001 FE	12	28	8	0.3	5100	2390	20
SS 6201 FE	12	32	10	0.6	6800	3050	36
SS 6301 FE	12	37	12	1.0	9700	4200	59
SS 6802 FE	15	24	5	0.3	2080	1260	7
SS 6902 FE	15	28	7	0.3	4300	2250	16
SS 6002 FE	15	32	9	0.3	5600	2840	30
SS 6202 FE	15	35	11	0.6	7650	3750	45
SS 6302 FE	15	42	13	1.0	11400	5450	81
SS 6803 FE	17	26	5	0.3	2630	1570	7
SS 6903 FE	17	30	7	0.3	4600	2550	17
SS 6003 FE	17	35	10	0.3	6000	3250	39
SS 6203 FE	17	40	12	0.6	9600	4800	63
SS 6303 FE	17	47	14	1.0	13600	6600	110
SS 6804 FE	20	32	7	0.3	4000	2460	17
SS 6904 FE	20	37	9	0.3	6400	3700	36
SS 6004 FE	20	42	12	0.6	9400	5050	65
SS 6204 FE	20	47	14	1.0	12800	6650	101
SS 6304 FE	20	52	15	1.1	15900	7850	142
SS 6805 FE	25	37	7	0.3	4300	2940	21
SS 6905 FE	25	42	9	0.3	7000	4550	42
SS 6005 FE	25	47	12	0.6	10100	5850	77
SS 6205 FE	25	52	15	1.0	14000	7900	127
SS 6305 FE	25	62	17	1.1	20600	11200	225
SS 6806 FE	30	42	7	0.3	4550	3400	24
SS 6906 FE	30	47	9	0.3	7250	5000	49
SS 6006 FE	30	55	13	1.0	13200	8300	114
SS 6206 FE	30	62	16	1.0	19500	11300	192
SS 6306 FE	30	72	19	1.1	26700	15000	342
SS 6807 FE	35	47	7	0.3	4750	3800	27
SS 6907 FE	35	55	10	0.6	10400	7200	74
SS 6007 FE	35	62	14	1.0	16000	10300	148
SS 6207 FE	35	72	17	1.1	25700	15400	276
SS 6307 FE	35	80	21	1.5	33300	19100	446



Bearing Numbers	d	D	B	r min.	Basic Load Ratings		Mass
					Cr	Cor	
	mm	mm	mm	mm	N	N	g
SS 6808 FE	40	52	7	0.3	4950	4200	30
SS 6908 FE	40	62	12	0.6	13700	9900	109
SS 6008 FE	40	68	15	1.0	16800	11600	186
SS 6208 FE	40	80	18	1.1	29100	17900	364
SS 6308 FE	40	90	23	1.5	40700	24000	616
SS 6909 FE	45	68	12	0.6	14100	10900	128
SS 6009 FE	45	75	16	1.0	21000	15100	237
SS 6209 FE	45	85	19	1.1	32700	20500	401
SS 6309 FE	45	100	25	1.5	53000	32000	811
SS 6910 FE	50	72	12	0.6	14500	11700	130
SS 6010 FE	50	80	16	1.0	21800	16600	254
SS 6210 FE	50	90	20	1.1	35100	23200	452
SS 6310 FE	50	110	27	2.0	62000	38200	1044
SS 6911 FE	55	80	13	1.0	16600	14100	184
SS 6011 FE	55	90	18	1.1	28300	21300	376
SS 6211 FE	55	100	21	1.5	43400	29400	584
SS 6311 FE	55	120	29	2.0	71600	44800	1336
SS 6912 FE	60	85	13	1.0	20200	17300	192
SS 6012 FE	60	95	18	1.1	29400	23200	405
SS 6212 FE	60	110	22	1.5	52400	36100	764
SS 6312 FE	60	130	31	2.1	81800	52000	1676
SS 6913 FE	65	90	13	1.0	17400	16000	209
SS 6013 FE	65	100	18	1.1	30500	25200	428
SS 6213 FE	65	120	23	1.5	57200	40000	975
SS 6914 FE	70	100	16	1.0	23700	21100	334
SS 6014 FE	70	110	20	1.1	38000	30900	596
SS 6214 FE	70	125	24	1.5	62200	44000	1049
SS 6915 FE	75	105	16	1.0	24300	22600	351
SS 6015 FE	75	115	20	1.1	39500	33500	622
SS 6916 FE	80	110	16	1.0	25000	23900	369
SS 6016 FE	80	125	22	1.1	47700	39700	833

Bearing
selectionProducts
SeriesAISI
440CAISI
304AISI
630High-
SiliconPure
Titanium

Ceramic

Heat
ResistanceGrease
FreeLow
TorqueSolid
GreaseWater-resistant
Food grade
GreaseClean room
GreaseVacuum
GreaseConductive
GreaseSet
ScrewAlignment
FunctionFlange
UnitGuide
WheelSpherical
Outer ring6800
6900SS5200
5200

5800

Customization

Examples
of Use